



ACCENDO LIGHTING

ILLUMINATION

- Adjustable, glare-free PAR-Type lamp heads.
- 6V model offers 7.2W lamps, standard.
- 12V 50W model offers 9W lamps, standard.
12V 100W model offers 12W lamps, standard.
- Remote head capable.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable Sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Knockouts on the back for wall mount.
- Side and top knockouts for conduit feed applications.

HOUSING

- Injection-molded, engineering-grade, 5VA flame retardant, high-impact thermoplastic construction.



OPTIONS

- HTR: Optional internal heater for cold temperature applications.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.

WARRANTY/LISTING

- Five Year Warranty on all electronics and housing. Battery pro-rated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL listed for dry locations. (25°C)

Ordering Information

ALBE

Voltage

Capacity

Options

6 - 6V

5 - 50W

HTR -(50W units only)

12 - 12V

10 - 100W

20SB -(12V20W Sealed beam halogen)

USA -(USA Assembled)



AL ALBE Emergency Light Remote Capable

Dimensions:

