



ACCENDO
LIGHTING



General Description:

The Accendo Lighting Stairwell Angle Wrap (ALAW) is an angled wrap stairwell luminaire suitable for damp locations with a timeless aesthetic design. The ALAW provides even light distribution with high lumen output and excellent color rendering to create visual comfort.



FEATURES

- Lumen packages ranging from 2000L to 9500L.
- Tunable White (TW) options available.
- 80 CRI standard, 90 CRI option available.

CONSTRUCTION

- 22 gauge white steel with die-cast end caps.
- Vandal resistant proprietary ribbed, frosted acrylic lens.
- Continuous rows are available (consult factory).

ELECTRICAL

- Voltage: 120-277V or 347-480V AC input
- Driver: Class 2, constant current, calibrated to lumen packages (0-10V dimming standard)
- Operation Temperature: -30°C (-22°F) to 40°C (104°F)²

CONTROLS

- On/Off occupancy sensor and programmable smart sensor with daylight harvesting available.
- Ultrasonic sensor with optional multi-level dimming available. User selectable standby options (10, 25 or 50%) and time delay adjustments (5, 10, 15 or 30 minutes).
- Consult factory for additional sensor options.

MOUNTING

- Surface (ceiling or wall) mount ready.

WARRANTY

- Backed by XtraLight's limited 5-year warranty.

Ordering Information

Ordering Example: ALRW-4-4000L-40K-DIM-SCA-EM-XLS

	Size	MODEL	CCT	Driver	Lens	Options	Series
ALRW	2 2 FT	2000L 3000L	30K 3000K 35K 3500K 40K 4000K 50K 5000K	DIM Dim 0-10V, 120-277V DIM1 1% Dim, 120-277V	SCA Smooth Clear acrylic SFA Smooth Frosted acrylic PFA Prismatic Frosted acrylic	EM Emergency Battery Back-up GTD Generator Transfer Device 90C 90CRI	XLS
	4 4 FT	2000L 4000L 5000L					
	8 8 FT	5000L 7000L 9000L					

1. Tunable White (TW) options not ETL listed.
2. Some models can achieve operating temperatures up to 40°C.
3. U provides ON/OFF operation.
4. MLD option must be ordered with the Ultrasonic sensor (U).

Additional:

DIMENSIONAL DATA

STANDARD SIZES

